

ACRYLIC LATEX BLOCK FILLER

For Interior Or Exterior Surfaces



Technical Data

PRODUCT DESCRIPTION

A premium quality product that primes and fills blocks and masonry in one operation. Latex Block Filler is a ready to use block filler for interior or exterior surfaces. It provides a firm base for interior and exterior application of epoxy coatings, enamels, alkyds and latex paint. **PROTECT FROM FREEZING**

FEATURES

- Water clean-up
- Easy to apply
- Durable
- High Build

PRODUCT DATA

Description	Results
Vehicle Type	Vinyl Acrylic
Colors	3781 Off White
Gloss	Low Gloss
V.O.C.	49 g/L
Weight/Gallon	14.1 pounds
Solids by Weight.....	70.7%
Solids by Volume.....	50.2%
Viscosity	130 KU
Flash Point	None
Dry Heat Resistance	250°F
Freight Classification	Not Regulated

APPLICATION DATA

Description	Results
Application.....	Spray, Brush or Roll
Recommended Thickness.....	16 mils DFT
Dry Time @ 77° F, 50% RH	
To Touch	1 - 4 hours
To Handle	8 hours
To Recoat	24 - 48 hours
Pot Life	N/A
Coverage.....	50 sf/gal at 16 mils DFT
Thinner	Apply as Packaged
Clean Up	Water

EQUIPMENT RECOMMENDATIONS

The following are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.

BRUSH & ROLLER (General): Multiple coats may be required to achieve desired appearance, Avoid excessive rebrushing or rerolling.

BRUSH: Use a good quality natural or synthetic.

ROLLER: Use a good quality natural or synthetic 1" to 1.25" nap roller cover with phenolic core.

SPRAY APPLICATION (General): The following spray equipment has been found suitable and is available from manufacturers such as Binks, DeVilbiss and Graco.

AIRLESS SPRAY:

Model	Pump Ratio	Fluid Tip	Fluid Pressure	Filter Mesh
Graco Bulldog	30:1	.019 - .029	1600 - 2000	25
Binks B 8D	35:1	.019 - .029	1600 - 2000	25

GENERAL SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, dirt, grease, wax, mildew, loose or flaking paint and other surface contaminants. Remove loose, peeling, flaking or scaling paint by scraping, sanding or wire brush or blasting.

Remove any mildew, wearing protective clothing, gloves and glasses by washing with a solution of 3 quarts warm water, 1 quart household bleach and 1/3 cup of detergent. Do not add ammonia! Rinse thoroughly.

DIRECTIONS FOR USE

THINNING: Normally applied as packaged. May be thinned with 1/2 pint water per gallon.

APPLICATION: Mix thoroughly before use. May be applied by brush, roller or spray. Always work to a wet edge. **DO NOT APPLY** when the surface or air temperature is below 50°F.

For best results, spray or roller application should be followed by brushing while coating is wet to fill pores and crevices.

DRYING TIME: Low temperature, high humidity, poor ventilation and thick films will retard drying.

CLEAN UP: Clean up skin, clothing, paint tools or spills immediately with soap and water. Dried material may be removed by scraping.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal laws.

HEALTH AND SAFETY

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

Manufacturer warrants that the standards and qualities of the product described herein will not vary by more than 10% from the tested results set forth above. **MANUFACTURER HEREBY EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY AND/OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.** Buyer must make its own determination of the suitability of any product for its use, whether such product is used alone or in combination with other materials. **To the extent this or any of Manufacturer's products is proven to be defective, Buyer's sole remedy shall be limited to the replacement of such defective product, exclusive of any costs of labor. MANUFACTURER SHALL NOT BE LIABLE OR OBLIGATED FOR ANY LOSS OR CONSEQUENTIAL OR OTHER DAMAGE INCURRED DIRECTLY OR INDIRECTLY BY BUYER OR ANY OTHER PERSON OR ENTITY THAT ARISES IN ANY WAY IN RELATION TO THIS OR ANY OF MANUFACTURER'S OTHER PRODUCTS.** Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority of the owner of the patent. No Applicator is or should be viewed as an employee or agent of Manufacturer. 08032011/AcrylicLatexBlockFillerTD.indd

JONES-BLAIR®/NEOGARD®

2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 350-7624 - www.jones-blair.com - www.neogard.com