

ACRYLIC LATEX BLOCK FILLER

For Interior Or Exterior Surfaces



Technical Data

PRODUCT DESCRIPTION

A premium quality product that primes and fills blocks and masonry in one operation. Latex Block Filler is a ready to use block filler for interior or exterior surfaces. It provides a firm base for interior and exterior application of epoxy coatings, enamels, alkyds and latex paint. **PROTECT FROM FREEZING**

FEATURES

- Water clean-up
- Easy to apply
- Durable
- High Build

PRODUCT DATA

Description	Results
Vehicle Type	Vinyl Acrylic
Colors	3781 Off White
Gloss	Low Gloss
V.O.C.	49 g/L
Weight/Gallon	14.1 pounds
Solids by Weight.....	70.7%
Solids by Volume.....	50.2%
Viscosity	130 KU
Flash Point	None
Dry Heat Resistance	250°F
Freight Classification	Not Regulated

APPLICATION DATA

Description	Results
Application.....	Spray, Brush or Roll
Recommended Thickness.....	16 mils DFT
Dry Time @ 77° F, 50% RH	
To Touch	1 - 4 hours
To Handle	8 hours
To Recoat	24 - 48 hours
Pot Life	N/A
Coverage.....	50 sf/gal at 16 mils DFT
Thinner	Apply as Packaged
Clean Up	Water

EQUIPMENT RECOMMENDATIONS

The following are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.

BRUSH & ROLLER (General): Multiple coats may be required to achieve desired appearance, Avoid excessive rebrushing or rerolling.

BRUSH: Use a good quality natural or synthetic.

ROLLER: Use a good quality natural or synthetic 1" to 1.25" nap roller cover with phenolic core.

SPRAY APPLICATION (General): The following spray equipment has been found suitable and is available from manufacturers such as Binks, DeVilbiss and Graco.

AIRLESS SPRAY:

Model	Pump Ratio	Fluid Tip	Fluid Pressure	Filter Mesh
Graco Bulldog	30:1	.019 - .029	1600 - 2000	25
Binks B 8D	35:1	.019 - .029	1600 - 2000	25

GENERAL SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, dirt, grease, wax, mildew, loose or flaking paint and other surface contaminants. Remove loose, peeling, flaking or scaling paint by scraping, sanding or wire brush or blasting.

Remove any mildew, wearing protective clothing, gloves and glasses by washing with a solution of 3 quarts warm water, 1 quart household bleach and 1/3 cup of detergent. Do not add ammonia! Rinse thoroughly.

DIRECTIONS FOR USE

THINNING: Normally applied as packaged. May be thinned with 1/2 pint water per gallon.

APPLICATION: Mix thoroughly before use. May be applied by brush, roller or spray. Always work to a wet edge. **DO NOT APPLY** when the surface or air temperature is below 50°F.

For best results, spray or roller application should be followed by brushing while coating is wet to fill pores and crevices.

DRYING TIME: Low temperature, high humidity, poor ventilation and thick films will retard drying.

CLEAN UP: Clean up skin, clothing, paint tools or spills immediately with soap and water. Dried material may be removed by scraping.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal laws.

HEALTH AND SAFETY

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyer's process. **SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED** as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of any product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. 06182009 AcrylicLatexBlockFillerTD.indd

JONES-BLAIR®/NEOGARD

2728 Empire Central - Dallas, TX 75235 - Telephone (214) 353-1600 - Fax (214) 350-7624 - www.jones-blair.com