

Material Safety Data Sheet

Revision Date: 09-02-2009

Product Code: 3036

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: RUST-NOT HP ACRYLIC SATIN NEUTRAL BASE
Product Code: 3036
Document ID: M3036
Company: JONES-BLAIR® Company
2728 Empire Central
Dallas, TX 75235
1-214-353-1600
Revision Number: 1
Prior Version Date: None
Chemical Family: Acrylic Latex Coating
Intended use: Industrial Maintenance Coating
Emergency Contact: ChemTrec Center
Emergency Phone: 1-800-424-9300

II. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: **WARNING!**

Routes of Entry:

- Inhalation
- Ingestion
- Skin contact
- Eye contact

Immediate (Acute) Health Effects by Route of Exposure:

Skin Contact: Can cause minor skin irritation.

Long-Term (Chronic) Health Effects:

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #
Calcium carbonate	7 - 13	471-34-1
Chlorite	1 - 5	1318-59-8

IV. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion: If swallowed, do not induce vomiting. Get medical attention immediately.

V. FIRE FIGHTING MEASURES

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
Fire and/or Explosion Hazards: Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.
Hazardous Combustion Products: Carbon monoxide, Carbon dioxide
Flash Point (°F/°C): 212 / 100

VI. ACCIDENTAL RELEASE MEASURES

Material Safety Data Sheet

Revision Date: 09-02-2009

Product Code: 3036

Personal Precautions and Equipment: Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. See MSDS sections III, XIII and XV for disposal considerations.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal.

VII. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Overexposure may be harmful. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Storage Technical Measures and Conditions: Store in a cool dry place. Keep container(s) closed.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures: Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure.

Respiratory Protection: General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product.

Skin Protection: Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact. Chemical Resistant gloves are recommended.

Control Parameters:

Chemical Name	ACGIH TLV-TWA	ACGIH STEL	OSHA PEL-TWA
Calcium carbonate			15 mg/m ³ TWA total dust; 5mg/m ³ TWA Respirable Dust

IX. PHYSICAL AND CHEMICAL PROPERTIES

Color: Colorless. Or, various colors if colorant is added. (Color additives do not affect product hazards.)

Physical State: Liquid

pH (target): 9

VOC (g/l) (Regulatory, Calculated): 83
(Actual, Calculated): 34

Viscosity: 80 - 90 KU

Solubility in Water: Complete; 100%

Freezing Point (°F): <= 32 °F

Octanol/Water Partition Coefficient: Not Available

Volatiles, % by Volume (Calculated): 62.67

Volatiles, % by weight (Calculated): 54.06

Wt/Gal: 9.4 - 9.8

Physical and Chemical Properties are calculated target or range values for single packaged items and do not represent compliance values for multi-component (mixed) systems.

X. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other

Material Safety Data Sheet

Revision Date: 09-02-2009

Product Code: 3036

Materials to Avoid/Chemical Incompatibility: sources of ignition. Contamination.
Polymerization: Acids
Hazardous Decomposition Products: Will not occur.
Carbon monoxide, Carbon dioxide

XI. TOXICOLOGICAL INFORMATION

Component Toxicology Data:

Chemical Name	CAS Number	LD50/LC50
Not Available		

Carcinogens:

Chemical Name	CAS Number	IARC	NTP	OSHA
Not applicable				

XII. ECOLOGICAL INFORMATION

Toxicity data, if available, are listed below.

XIII. DISPOSAL CONSIDERATIONS

Disposal Methods: Refer to other sections of this MSDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

XIV. TRANSPORTATION INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint, Not-Regulated

XV. REGULATORY INFORMATION

United States Federal Regulations:

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

SARA EHS Chemicals	CAS #	%
Ammonia	7664-41-7	0.1 - 1

CERCLA
Not applicable

SARA 313
Not applicable

SARA 311/312

Health (Acute):	Y
Health (chronic):	N
Fire (Flammable):	N
Pressure:	N
Reactivity:	N

U. S. State Regulations:

Material Safety Data Sheet

Revision Date: 09-02-2009
Product Code: 3036

California Prop 65 Chemicals

	<u>CAS #</u>	<u>%</u>
Cancer Crystalline Silica	14808-60-7	0.01 - 0.1
Reproductive Butyl Benzyl Phthalate	85-68-7	0.1 - 1

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances List.

XVI. ADDITIONAL INFORMATION

Prepared By: Regulatory Department
Disclaimer: This MSDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.
Print Date: September 24, 2009